


## HS25CLR

**Term Tech Heatshrink 2:1 Ratio 25.4mmØ  
Expanded, 12.7mmØ Recovered Clear (Per  
Metre)**



The Termination Technology range of thin wall Cross linked Polyolefin Heatshrink is designed for commercial use with common uses including insulation, wire bundling, colour coding and mechanical protection. Available in a range of colours and sizes, all cut to metre as required. Specialist Heatshrink end caps, breakout boots, joints and adhesive lined versions also available from stock.



## Technical Data

### Colour and Material

Material	Crosslinked Polyolefin
Colour	Clear

### Dimensions

Led Flat Width (mm)	43
---------------------	----

### Durability

Chemical Resistance	Resistant to common fluids and solvents
Fungus Resistance	Tested with no growth occurring

### Electrical Ratings

Dielectric Strength (kV/mm)	Min 19.7 Tested to ASTM D-2671
Volume Resistivity (Ohm/cm)	Min $10^{13}$ Tested to ASTM D-876

### Physical Attributes

Adhesive Lined	No
----------------	----

### Product Specification

CE Compliant	Yes
ROHS Compliant	Yes

### Temperature and Fire Information

Continuous Operating Temperature (°C)	-55 to +135
Shrink Temperature (°C)	+90 to Start Shrinking
Fire Rating	UL224 VW-1; MIL-I-23053/5 Class 1 & 3

