

Data sheet

ID	FXKVM TR
Description	slip type coupler
Properties	for sandtight connections of FXKVR and FXKVS ductings
Colour	transparent
Classification	N 450, IP 40



Norms: ÖVE/ÖNORM EN 61386-1:2009, ÖVE/ÖNORM EN 61386-24:2011



Operating temperature		UV-Level		
-30 bis +70 °C		L2		
Art. no.	Inner diameter	Outer diameter	Small Package	Large Package
103 649	110 mm	129 mm	-	-
100 004	160 mm	173,9 mm	-	-

Further technical details

Details

With rubber seal	False
Surface protection	Untreated
Surface polished	False
Material	PE

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.