

TKE/B 32

Tails Kit Brass M32 with multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Brass nickel-plated
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66, IP68 (5 bar 30 min)
Surface	Nickel-plated
Thread type	M
Ø Connection thread D	32
Lead	1,5
Length screw-in thread L	8 mm
Key width SW	36 mm
Total length TL	36 mm - 44 mm
Type of cable anchorage	A
Install. torques fitting	20 N/m
Install. torques cap nut	20 N/m
Impact category	6
Order no. nickel-plated	10106232
Type	TKE/B 32
Packing unit	1
ETIM-Classification	EC000441

Description:

IP68 Brass cable gland. EMSKV 32/ MFD 2 x 9 mm Tails and 1 x 6 mm Earth. Kit contains multiple sealing insert, locknut and blanking insert.

28.12.2024

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk